


COMh-m7RP (E2)



COM-HPC® Mini with 13th Generation Intel® Core™ Processors

- ▶ High performance on small form factor
- ▶ Up to 64 GByte LPDDR5 6000 MT/s - In-Band ECC
- ▶ 16 PCIe lanes
- ▶ 2x 2.5 GbE with TSN support
- ▶ Optional NVMe SSD onboard
- ▶ Industrial grade temperature

	13TH GEN RAPTOR LAKE H-SERIES (45W)		
CPU	i7-13800HRE	i5-13600HRE	i3-13300HRE
CORES	14	12	8
NUMBER OF P-CORES	6	4	4
FREQUENCY BASE/TURBO (P-CORES)	2.5/5.0 GHz	2.7/4.8 GHz	2.1/4.6 GHz
NUMBER OF E-CORES	8	8	4
FREQUENCY BASE/TURBO (E-CORES)	1.8/4.0 GHz	1.9/3.6 GHz	1.5/3.4 GHz
TDP	45/35 W		
CACHE	24 MByte	18 MByte	12 MByte
IBECC	yes		
TCC/TSN	yes		
TJUNCTION MIN	-40°C		
TJUNCTION MAX	100°C		
USE CONDITION	Embedded / Industrial*		
	13th GEN RAPTOR LAKE P-SERIES (28W)		
CPU	i7-1370PRE	i5-1350PRE	i3-1320PRE
CORES	14	12	8
NUMBER OF P-CORES	6	4	4
FREQUENCY BASE/TURBO (P-CORES)	1.9/4.8 GHz	1.8/4.6 GHz	1.7/4.5 GHz
NUMBER OF E-CORES	8	8	4
FREQUENCY BASE/TURBO (E-CORES)	1.2/3.7 GHz	1.3/3.4 GHz	1.2/3.3 GHz
TDP	28/20 W		
CACHE	24 MByte	12 MByte	12 MByte
IBECC	yes		
TCC/TSN	yes		
TJUNCTION MIN	-40°C		
TJUNCTION MAX	100°C		
USE CONDITION	Embedded / Industrial*		
	13TH GEN RAPTOR LAKE U-SERIES (15W)		
CPU	i7-1365URE	i5-1345URE	i3-1315URE
CORES	10	10	6
NUMBER OF P-CORES	2	2	2
FREQUENCY BASE/TURBO (P-CORES)	1.7/4.9 GHz	1.4/4.6 GHz	1.2/4.5 GHz
NUMBER OF E-CORES	8	8	4
FREQUENCY BASE/TURBO (E-CORES)	1.2/3.7 GHz	1.1/3.4 GHz	0.9/3.3 GHz
TDP	15/12 W		
CACHE	12 MByte	12 MByte	10 MByte
IBECC	yes		
TCC/TSN	yes		
TJUNCTION MIN	-40°C		
TJUNCTION MAX	100°C		
USE CONDITION	Embedded / Industrial*		

*For Industrial use condition turbo needs to be disabled

PART NO.	CPU	LPDDR5 MEMORY DOWN	ETH PHY	DDI	USB 4.0	USB 3.2 Gen2	FLASH - NVME	OP.TEMP.
HM702-3200-80-7	i7-13800HRE	32 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-60-5	i5-13600HRE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-30-3	i3-13300HRE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-3200-70-7	i7-1370PRE	32 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-50-5	i5-1350PRE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-20-3	i3-1320PRE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-65-7	i7-1365URE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-1600-45-5	i5-1345URE	16 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C
HM702-0800-15-3	i3-1315URE	8 GB	2 x2.5GbE	1	2	2	no	-40 °C - 85 °C

Please contact your sales representative for other versions

Carrier

ARTICLE	PART NO.	DESCRIPTION
COMh/MINI EVALUATION CARRIER	HM701-0000-10-0	COM-HPC® Evaluation Carrier Mini

Cooling

ARTICLE	PART NO.	DESCRIPTION
HSP COMh-m7RP (E2) THREAD	HM702-0000-99-0	Heatspreader for COMh-m7RP commercial and E2, Cu-core, threaded mounting holes
HSP COMh-m7RP (E2) THROUGH	HM702-0000-99-1	Heatspreader for COMh-m7RP commercial and E2, Cu-core, through mounting holes
COMh Mini active uni cooler (W/O HSP)	HM799-0000-99-0	COM-HPC® Universal Active Cooler for Heatspreader Mounting
COMh Mini passive uni cooler (W/O HSP)	HM799-0000-99-1	COM-HPC® Universal Passive Cooler for Heatspreader Mounting

Global Headquarters

Kontron Europe GmbH

Gutenbergstraße 2
 85737 Ismaning, Germany
 Tel.: + 49 821 4086-0
 info@kontron.com

www.kontron.com

